

10-16米柴动剪叉式高空作业平台

10-16m Diesel Scissor Lifts

- 大马力柴油发动机，四轮驱动，越野性能强劲；
Powerful diesel engine, 4-wheel drive, strong off-road performance;
- 液压一键调平支腿，稳定性强，适应复杂工况；
Hydraulic one-button leveling outriggers bring strong stability;
- 双延伸大平台，大载荷，扩大作业范围，提高生产力；
Double-extended platform, large load with wider work scope.



技术参数(Technical Parameters)

10-16米柴动剪叉式高空作业平台/10-16m Diesel Scissor Lifts

型号 Model	Z10D	Z13D	Z16D
尺寸 Measurements			
最大工作高度 Max. Working Height	12m	15m	18m
最大平台高度 Max. Platform Height	10m	13m	16m
平台尺寸 (L*W) Platform Dimensions	3.95×1.83m	3.95×1.83m	3.95×1.83m
长度-收起状态 Length-stowed	4.2/4.81m	4.2/4.81m	4.2/4.81m
宽度-收起状态 Width-stowed	2.28m	2.28m	2.28m
高度-收起状态 Height-stowed	2.81m	3.03m	3.25m
护栏折叠后高度 Height -stowed (folding guardrails)	2.12m	2.34m	2.56m
平台水平延伸 Slide-out Platform Extension Deck - Length	1.22/1.52m	1.22/1.52m	1.22/1.52m
离地间隙-Ground Clearance	0.23m	0.23m	0.23m
轴距 Wheelbase	2.84m	2.84m	2.84m
整机重量Weight	6850kg	7350kg	8850kg
性能 Productivity			
最大承载能力 Max. Lift Capacity	1150kg	680kg	680kg
最大承载能力-延伸平台 Lift capacity - Extension Deck Extended	230kg	230kg	230kg
最大承载人数 Max. Platform Occupancy	7	5	5
行驶速度-收车状态 Drive Speed-Stowed	6.3km/h		
行驶速度-举升状态 Drive Speed-Raised	1.1km/h		
爬坡度-收车状态 Gradeability -Stowed	45%		
最大工作坡度 Max. Working Angel	3°/3°		
转弯半径 Turning Radius -Inside/Outside	2.78/4.95m		
实心无痕轮胎 Tires - Solid Non-Marking	33×12-20		
动力 Power			
发动机型号 Engine	洋马4TNV94L-B×PHZ		
功率 Power	35.5Kw/2600rpm		
燃油箱容积 Fuel Tank Volume	115L		
液压油箱容积Hydraulic tank volume	170L		
控制电压 Control Voltage	12V		
符合标准 Standards Compliance	EN280:2013+A1:2015 GB25849-2010		