

Telescopic Mast Lift



- Proportional Controls
- Emergency Stop Button
- Emergency Lowering System
- Automatic Brake System
- Onboard Diagnostic System
- Non-Marking Tyre
- Drivable At Full Height
- Cylinder Holding Valve
- Automatic Pothole Protection

Model	M3.6	M4.8	M6.0
Measurements			
Max. Working Height	5.6m	6.8m	8.0m
Max. Platform Height	3.6m	4.8m	6.0m
Length-stowed	1.36m	1.36m	1.36m
Width-stowed	0.76m	0.76m	0.82m
Height-stowed	1.7m	1.98m	1.98m
Platform Dimensions	1.3×0.7×1.1m	1.3×0.7×1.1m	1.3×0.7×1.1m
Ext. Platform Length	0.51m	0.51m	0.51m
Wheelbase	1.04m	1.04m	1.04m
Weight	810kg	980kg	1060kg
Productivity			
Max. Lift Capacity	227kg	227kg	159kg
Ext. Platform Capacity	114kg	114kg	114kg
Ground Clearance-Stowed	0.1m	0.1m	0.1m
Ground Clearance-Raised	0.023m	0.023m	0.023m
Inner Turning Radius	0	0	0
Outer Turning Radius	1.4m	1.4m	1.4m
Lifting Motor	24V DC/1.3KW	24V DC/1.3KW	24V DC/1.3KW
Drive Motor	2X24V DC/0.5KW	2X24V DC/0.5KW	2X24V DC/0.5KW
Drive Speed-Stowed	4km/h	4km/h	4km/h
Drive Speed-Raised	1.1km/h	1.1km/h	1.1km/h
Up/Down Speed	31/32 sec	41.5/42 sec	52/53 sec
Gradeability	25%	25%	25%
Max. Working Angle	1.5°	1.5°	2°
Tires Tyres	φ305×100mm	φ305×100mm	φ305×100mm
Power			
Battery	2×12V/100Ah	2×12V/100Ah	2×12V/100Ah
Charger	24V/15A	24V/15A	24V/15A